

4.5 mm & 6.5 mm Cannulated Cancellous Screws



Indication:

4.5 mm CC screws:

- Fixation of malleolar fracture.
- Fixation of calcaneus & talus fracture.
- Fixation of tibial plateau fractures.
- For carpal and tarsal arthrodesis.
- Fixation of pilon tibial fractures.

6.5 mm CC screws:

- Fixation of femur neck fracture.
- Fixation of intercondylar femur fracture.
- Fixation of iliosacral dislocation.
- For ankle arthrodesis.
- Fixation of epiphysiolysis of femoral head.

Features:

- 6.5 CC screws available in short and long thread.
- All cc screws possess reverse cutting flute.
- Fixation can be done with and without washer.
- 1.5 mm guidewire can be used for 4.5 cc screws and 2.5 mm guide wire can be used for 6.5 mm cc screws.

Ø4.5 mm Cannulated Screws, partially threaded

Length 20mm ST039.20	Length 38mm ST039.38	Length 56mm ST039.56
----------------------------------	----------------------------------	----------------------------------

Length 22mm ST039.22	Length 40mm ST039.40	Length 60mm ST039.60
----------------------------------	----------------------------------	----------------------------------

Length 24mm ST039.24	Length 42mm ST039.42	Length 64mm ST039.64
----------------------------------	----------------------------------	----------------------------------

Length 26mm ST039.26	Length 44mm ST039.44	Length 68mm ST039.68
----------------------------------	----------------------------------	----------------------------------

Length 28mm ST039.28	Length 46mm ST039.46	Length 72mm ST039.72
----------------------------------	----------------------------------	----------------------------------

Length 30mm ST039.30	Length 48mm ST039.48	Length 74mm ST039.74
----------------------------------	----------------------------------	----------------------------------

Length 32mm ST039.32	Length 50mm ST039.50	Length 76mm ST039.76
----------------------------------	----------------------------------	----------------------------------

Length 34mm ST039.34	Length 52mm ST039.52	Length 78mm ST039.78
----------------------------------	----------------------------------	----------------------------------

Length 36mm ST039.36	Length 54mm ST039.54	Length 80mm ST039.80
----------------------------------	----------------------------------	----------------------------------



4.5 mm & 6.5 mm Cannulated Cancellous Screws



Ø6.5 mm Cannulated Screws, 16 mm partially threaded

Length 30mm ST040.30	Length 65mm ST040.65	Length 100mm ST040.100
Length 35mm ST040.35	Length 70mm ST040.70	Length 105mm ST040.105
Length 40mm ST040.40	Length 75mm ST040.75	Length 110mm ST040.110
Length 45mm ST040.45	Length 80mm ST040.80	Length 115mm ST040.115
Length 50mm ST040.50	Length 85mm ST040.85	Length 120mm ST040.120
Length 55mm ST040.55	Length 90mm ST040.90	
Length 60mm ST040.60	Length 95mm ST040.95	

Ø6.5 mm Cannulated Screws, 32 mm partially threaded

Length 45mm ST107.45	Length 85mm ST107.85
Length 50mm ST107.50	Length 90mm ST107.90
Length 55mm ST107.55	Length 95mm ST107.95
Length 60mm ST107.60	Length 100mm ST107.100
Length 65mm ST107.65	Length 105mm ST107.105
Length 70mm ST107.70	Length 110mm ST107.110
Length 75mm ST107.75	Length 115mm ST107.115
Length 80mm ST107.80	Length 120mm ST107.120

